

# Emulex<sup>®</sup> 900 Series

PRODUCT INFORMATION BROCHURE

Emulex 900 Series is a detonator sensitive emulsion explosive with putty like texture packaged in plastic film, tampable plastic film or rigid paper tube cartridges..

## ADVANTAGES

- Excellent fragmentation when proper grade is matched to the rock conditions.
- >99% borehole coupling when loading cut or tamped cartridges.
- Excellent water resistance in all grades.
- Superior resistance to dynamic pre-compression.



## PROPERTIES

Product	Density [g/cc]	RBS <sup>‡</sup>	Fume Class	Water Resistance	VOD	
					[ft/s]	[m/s]
<b>Emulex 917</b>	1.17	107	1	Excellent	17,000	5,577
<b>Emulex 927</b>	1.17	142	2	Excellent	16,500	5,413

<sup>‡</sup> Energy is calculated using TIGER, a thermo-dynamic computer code used by Austin Powder Company. Other computer codes may give different values. ANFO = 100 @ 0.82 g/cc.

## PRIMING

Use a high strength detonator (Rock★Star<sup>®</sup>, Shock★Star<sup>®</sup> or equivalent). If product temperature is below 0° F (-17° C), prime with a minimum of a Gold Nugget<sup>™</sup> (8 gm) cast booster. This product is not designed for use with any strength of detonating cord.



**AUSTIN POWDER**

Austin Powder Company, 25800 Science Park Drive, Cleveland, OH 44122

Phone: 1-800-321-0752 | Fax: 1-216-464-4418 | Email: info@austinpowder.com | www.austinpowder.com



# Emulex 900 Series

## STANDARD TECHNICAL DESCRIPTION

Detonator sensitive emulsion

## STANDARD PACKAGING DETAILS

Cartridge Size		917	927	Cartridge Weight		Case Count 50 lb/22.5 kg
[in]	[mm]			[lb]	[kg]	
1 x 12	25 x 300	V, PMP	V, PMP	0.38	0.17	132
1 ¼ x 12	32 x 300	V, PMP	V, PMP	0.67	0.30	75
1 ½ x 12	38 x 300	V, PMP	V, PMP	0.88	0.40	57
1 ¼ x 16	32 x 400	---	AT	0.89	0.40	56
1 ½ x 16	38 x 400	V, PMP	V, AT, PMP	1.28	0.58	39
1 ¾ x 16	44 x 400	V	V, AT	1.61	0.73	31
2 x 16	50 x 400	V	V, BN	2.27	1.03	22
2 ¼ x 16	57 x 400	V	V, BN	2.50	1.13	20
2 ½ x 16	63 x 400	V	V, BN	3.33	1.51	15
2 ¾ x 16	69 x 400	V	V, BN	3.85	1.75	13
3 x 16	75 x 400	V	V, BN	4.55	2.06	11
3 ¼ x 16	82 x 400	V	V, BN	5.00	2.27	10
3 ½ x 16	88 x 400	V	V, BN	6.25	2.84	8

V = Plastic Film; PMP = Poly Mylar Poly Laminate Film (tampable);  
AT, BN = Rigid Paper Tube

--- Not Available

Note: All dimensions and weights are nominal.

## STORAGE

Store in accordance with all applicable local, state, provincial and federal laws.

## SHELF LIFE

One year from date of manufacture under good storage conditions.

## TRANSPORTATION DATA

### UN CLASSIFICATION

Shipping Name: Explosive, Blasting, Type E

Class & Division: 1.1D

ID Number: UN0241

### US DOT REFERENCE NUMBER

EX-9305177

**Disclaimer of Warranties and Limitations of Liabilities:** Products described in this bulletin are sold by Austin Powder Company without warranty; express, implied or statutory or as to MERCHANTABILITY, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for loss of anticipated profits, consequential damages or incidental damages.

© 2022 Austin Powder Company. All rights reserved.

For more information and service locations in your area, please contact Austin Powder Company's headquarters:



## AUSTIN POWDER

Austin Powder Company, 25800 Science Park Drive, Cleveland, OH 44122

Phone: 1-800-321-0752 | Fax: 1-216-464-4418 | Email: [info@austinpowder.com](mailto:info@austinpowder.com) | [www.austinpowder.com](http://www.austinpowder.com)

1/2/02 | r 01/31/2020

