# CoalStar 30

## PRODUCT INFORMATION BROCHURE

COALSTAR 30 are permissible millisecond electric detonators. These detonators are specifically designed for use in environments where there is an ignition hazard associated with air-methane and air-coal mixtures. Accuracy of delay times eliminates overlap any contributes significantly to breakage and vibration control when properly used. The timing range consists of 17 delay numbers.



## **BENEFITS**

- Multi-step quality control program for testing of components and finished products to ensure reliable field performance.
- Detonators are easy to handle, the yellow color of leg wires making it easier to use in underground environments with limited visibility.
- High impact protection.

## **PROPERTIES**

## Delay sequence

Delay #	0	1	2	3	4	5	6	7	8
Nominal delay (ms)	0	30	60	90	120	150	180	210	240
Delay #	9	10	11	12	13	14	15	16	
Nominal delay (ms)	270	300	330	360	390	420	450	480	

## **FIRING PARAMETERS**

Туре	Group I	Group II	Group III
Fusehead resistance	1.50 - 1.90 Ω	0.52 – 0.60 Ω	0.16 – 0.20 Ω
No fire current	0.18 A	0.45 A	1.2 A
No fire energy	0.8 mJ/Ω	8 mJ/Ω	80 mJ/Ω
All fire current	1 A	1.5 A	3.5 A
All fire energy in series	2.5 mJ/Ω	16 mJ/Ω	140 mJ/Ω

In case of use of electric detonators in applications with a risk of initiation from stray currents, the appropriate detonator sensitivity must be chosen.







#### PRODUCT INFORMATION BROCHURE

## STANDARD TECHNICAL DESCRIPTION

Detonator standard shell material	Copper	
Base charge	600 mg	
Leg wires insulation material	PVC	
Water pressure resistance	0.3 MPa / 24 hours	
Temperature range for application	-30 °C < T < +60 °C	
Shelf life (storage conditions)	2 years (-30 °C to 40 °C)	
Label marking	Delay #, Detonator type, Delay ms, Wire length, Data matrix code (traceability)	
Notified body	CE 0589	
Alternative name	instantaneous detonators: 0-N-ZB, 0-S-ZB ms detonators: DEM-N-ZB, DEM-S-ZB	

## STANDARD PACKAGING DETAILS

Wire length (m)	Packaging 1	.4B UN 0255	Packaging 1.4S UN 0456		
	Cu ø 0.5 mm	Cu ø 0.6 mm Fe ø 0.65 mm	Cu ø 0.5 mm	Cu ø 0.6 mm Fe ø 0.65 mm	
2 / 3	500		175		
5	300		150		

COALSTAR 30 detonators are packaged in cardboard box of outer dimension 425x305x250 mm. Other wire lengths are possible on demand.

Contact your local Austin Powder representative for further information.

#### Disclaimer of Warranties and Limitations of Liabilities

The data set forth in this Product Information Brochure (PIB) are based on the product test procedures of Austin Detonator s.r.o. in use at the time of publication of this PIB. Specifications, test values and information are exclusively non-binding preliminary information and are not guaranteed; the actual data may differ for various reasons (e.g. temperature, humidity, pressure). Technical inaccuracies or typographical errors and the right to amend the PIB at any time without notice shall be reserved. Austin Detonator s.r.o. does not assume any liability, covenants, guaranties or warranties with respect to the completeness, accuracy, reliability, suitability or availability of the product and the information of the PIB.

Any liability for damages of any kind (such as direct or indirect, incidental or consequential damages, losses or expenses), directly or indirectly related for any reason to this PIB or the use of the products is excluded. The customer is (even when making decisions based on the information in the PIB) solely responsible for the proper use of the potentially dangerous products that, accordingly, may only be used by trained personnel and in compliance with applicable law. To the entire legal relationship between their customers and Austin Detonator s.r.o. their (Austin's) general terms and conditions (they can be downloaded from the homepage www.austin.cz) shall apply.



04/2018