


# Shock★Star TS

## PRODUCT INFORMATION BROCHURE

**SHOCK★STAR TS** detonator products are available in a sequence of 40 delays from 25 ms to 9,000 ms.

Austin's TS delay sequence is appropriate for applications such as tunneling and shaft or raise mining where long delays are required between holes to allow for movement of broken rock.



They are designed to be used as in-hole detonators for the initiation of cast boosters and high explosives. In-hole delays may be equipped with a J-hook for compatibility with detonating cord initiation.

### BENEFITS

- 720 mg base charge.
- High impact protection.
- Manufactured with bright yellow shock tube for high visibility.
- Excellent delay time accuracy ensures greater than 99% probability of in-sequence initiation.

### PROPERITES

Delay sequence

<b>Delay #</b>	<b>0</b>	<b>1</b>	<b>1<sup>1/2</sup></b>	<b>2</b>	<b>2<sup>1/2</sup></b>	<b>3</b>	<b>3<sup>1/2</sup></b>	<b>4</b>
Nominal delay (ms)	25	100	150	200	250	300	350	400
<b>Delay #</b>	<b>4<sup>1/2</sup></b>	<b>5</b>	<b>5<sup>1/2</sup></b>	<b>6</b>	<b>6<sup>1/2</sup></b>	<b>7</b>	<b>7<sup>1/2</sup></b>	<b>8</b>
Nominal delay (ms)	450	500	550	600	650	700	750	800
<b>Delay #</b>	<b>8<sup>1/2</sup></b>	<b>9</b>	<b>9<sup>1/2</sup></b>	<b>10</b>	<b>11</b>	<b>12</b>	<b>14</b>	<b>16</b>
Nominal delay (ms)	850	900	950	1,000	1,100	1,200	1,400	1,600
<b>Delay #</b>	<b>18</b>	<b>20</b>	<b>25</b>	<b>30</b>	<b>35</b>	<b>40</b>	<b>45</b>	<b>50</b>
Nominal delay (ms)	1,800	2,000	2,500	3,000	3,500	4,000	4,500	5,000
<b>Delay #</b>	<b>55</b>	<b>60</b>	<b>65</b>	<b>70</b>	<b>75</b>	<b>80</b>	<b>85</b>	<b>90</b>
Nominal delay (ms)	5,500	6,000	6,500	7,000	7,500	8,000	8,500	9,000



## AUSTIN POWDER

Tenaga Kimia-Austin Detonator Sdn. Bhd. (580221-P)  
(formerly known as Tenaga Kimia-Ensign Bickford Sdn Bhd)

No. 8, Jalan SS 22/21, Damansara Jaya, 47400 Petaling Jaya, Selangor Darul Ehsan. Tel : 603 - 7729 7464 | Fax : 603 - 7729 8383

# Shock★Star TS

## PRODUCT INFORMATION BROCHURE

### STANDARD TECHNICAL DESCRIPTION

<b>DETONATOR</b>	
Detonator shell material	Aluminum
Base charge	720 mg
Water pressure resistivity	0.3 MPa / 7 days
Temperature range for application	from -30 °C to +60 °C
Shelf life (storage conditions)	2 years (-30 °C to +40 °C, R.H. max. 65%) in original, sealed package
Label marking	Delay #, Detonator type, Delay ms, ST length, Oder number
<b>SHOCK TUBE</b>	
Velocity of detonation	2,000 ± 100 m/s
Color	Yellow

### STANDARD PACKAGING DETAILS

Shock tube length (m)	LP 1.1B UN 0360		Shock tube length (m)	LP 1.4S UN 0500	
	Lasso	Fig 69		Lasso	Fig 69
	Units / Box			Units / Box	
2.4	180	180	2.4	100	100
3.6	140	140	3.6	100	100
4.8	120	100	4.8	80	80
7.2	80	90	7.2	55	50
9	80	80	9	50	50
12	60	60	12	40	40

SHOCK★STAR TS detonators are packaged in cardboard carton of outer dimension 385x235x282 mm.

Contact your local Austin Powder representative for further information.

#### Disclaimer of Warranties and Limitations of Liabilities

The data set forth in this Product Information Brochure (PIB) are based on the product test procedures of Tenaga Kimia-Austin Detonator Sdn Bhd in use at the time of publication of this PIB. Specifications, test values and information are exclusively non-binding preliminary information and are not guaranteed; the actual data may differ for various reasons (e.g. temperature, humidity, pressure). Technical inaccuracies or typographical errors and the right to amend the PIB at any time without notice shall be reserved. Tenaga Kimia-Austin Detonator Sdn Bhd, its subsidiaries and distributors do not assume any liability, covenants, guaranties or warranties with respect to the completeness, accuracy, reliability, suitability or availability of the product and the information of the PIB.

Any liability for damages of any kind (such as direct or indirect, incidental or consequential damages, losses or expenses), directly or indirectly related for any reason to this PIB or the use of the products is excluded. The customer is (even when making decisions based on the information in the PIB) solely responsible for the proper use of the potentially dangerous products that, accordingly, may only be used by trained personnel and in compliance with applicable law. To the entire legal relationship between their customers and Tenaga Kimia-Austin Detonator Sdn Bhd their (TKAD) general terms and conditions (please refer to standard terms of sale) shall apply.



## AUSTIN POWDER

Tenaga Kimia-Austin Detonator Sdn. Bhd. (580221-P)  
(formerly known as Tenaga Kimia-Ensign Bickford Sdn Bhd)

No. 8, Jalan SS 22/21, Damansara Jaya, 47400 Petaling Jaya, Selangor Darul Ehsan. Tel : 603 - 7729 7464 | Fax : 603 - 7729 8383

06/2020

