

# ShockTube

PRODUCT INFORMATION BROCHURE

**SHOCKTUBE** allows a non-electric system from the point of initiation all the way through the blast. SHOCKTUBE is available on 150, 300, 500 and 3000 m spools to permit a single splice free signal line between the initiation point and the blast pattern.



## **BENEFITS**

- Manufactured with three layer shock tube
- Initiates consistently and silently at 2,000 m/s
- Packaged on sturdy spools for durability during shipping and multiple use.



## **AUSTIN POWDER**

Tenaga Kimia-Austin Detonator Sdn. Bhd. (580221-P)  
(formerly known as Tenaga Kimia-Ensign Bickford Sdn Bhd)

No. 8, Jalan SS 22/21, Damansara Jaya, 47400 Petaling Jaya, Selangor Darul Ehsan. Tel : 603 - 7729 7464 | Fax : 603 - 7729 8383

# ShockTube

## PRODUCT INFORMATION BROCHURE

### STANDARD TECHNICAL DESCRIPTION

Outer diameter	Ø 3 ± 0.2 mm
Explosive weight per meter	17 ± 5 mg HMX/AL per meter
Velocity of detonation	2,000 ± 250 m/s
Colour	Yellow / Red
Tensile strength	> 150 N
Temperature range for application	from -30 °C to +60 °C
Shelf life (storage conditions)	2 years (0 °C to +40 °C, R.H. from 30% to 50%) in original packaging

### STANDARD PACKAGING DETAILS

Shock tube length (m) on spools	Units / Box	Box dimensions (mm)
150	1	385x235x282
300	1	385x235x282
500	1	400x400x250
3000	1	445x445x370

SHOCKTUBE spools are packaged in cardboard carton box of outer dimensions described above.

Contact your local Austin Powder representative for further information.

#### Disclaimer of Warranties and Limitations of Liabilities

The data set forth in this Product Information Brochure (PIB) are based on the product test procedures of Tenaga Kimia-Austin Detonator Sdn Bhd in use at the time of publication of this PIB. Specifications, test values and information are exclusively non-binding preliminary information and are not guaranteed; the actual data may differ for various reasons (e.g. temperature, humidity, pressure). Technical inaccuracies or typographical errors and the right to amend the PIB at any time without notice shall be reserved. Tenaga Kimia-Austin Detonator Sdn Bhd, its subsidiaries and distributors do not assume any liability, covenants, guaranties or warranties with respect to the completeness, accuracy, reliability, suitability or availability of the product and the information of the PIB.

Any liability for damages of any kind (such as direct or indirect, incidental or consequential damages, losses or expenses), directly or indirectly related for any reason to this PIB or the use of the products is excluded. The customer is (even when making decisions based on the information in the PIB) solely responsible for the proper use of the potentially dangerous products that, accordingly, may only be used by trained personnel and in compliance with applicable law. To the entire legal relationship between their customers and Tenaga Kimia-Austin Detonator Sdn Bhd their (TKAD) general terms and conditions (please refer to standard terms of sale) shall apply.



## AUSTIN POWDER

Tenaga Kimia-Austin Detonator Sdn. Bhd. (580221-P)  
(formerly known as Tenaga Kimia-Ensign Bickford Sdn Bhd)

No. 8, Jalan SS 22/21, Damansara Jaya, 47400 Petaling Jaya, Selangor Darul Ehsan. Tel : 603 - 7729 7464 | Fax : 603 - 7729 8383

06/2020

