

# PRODUCT INFORMATION BROCHURE

# **DBM1600-2-K**



The DBM1600-2-K Blasting
Machine is a multipurpose device
designed to work with E★STAR
detonators. Its main functions are to
verify, charge and fire all detonators in
all branches, up to 1,600 E★STAR
detonators per blast. When
connected to a second DBM1600-2-K
via the DIM-1 module in master-slave
mode, it is possible to fire up to 3,200
E★STAR detonators per blast.

### PRODUCT OVERVIEW

## **PROPERTIES**

- Verifies all detonators.
- Change detonator delays.
- Charge detonator capacitors.
- Fires detonators.
- Transfer data from Logger / Loggers.
- Transfer data to PC for post processing.

#### **ADVANTAGES**

- All detonators are verified prior to firing.
- Downloadable data after firing.
- Large buttons suitable for use with gloves.
- Water resistant.

#### STANDARD TECHNICAL DESCRIPTION

Name	DBM1600-2-K
Weight	11.5 lbs / 5,300 g
Size	10.5 x 10 x 7 in / 270 x 250 x 180 mm
Case	ABS plastic
Battery	9 x NiMH (rechargeable), built-in
Charging	Mains charger (100 – 240 V; 50 – 60 Hz) Car charger (11 – 16 V system)
Operation voltage	42.5 V
Operation current	0.55 mA (programming), 150 mA (verification)
Temperature range for application	From -22°F to 140°F (-30°C to +60°C) Slower display reaction in temperatures under -4°F (-20°C)
Storage condition	From 32°F to 104°F (0°C to +40°C) R.H. max. 80%
Firing capabilities	Maximum 1,600 detonators (normal mode, single blasting machine) Maximum 3,200 detonators (master-slave mode, two blasting machines)

Disclaimer of Warranties and Limitations of Liabilities: Products described in this document are sold by Austin Powder without warranty; express, implied or statutory or as to MERCHANTABILITY, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for loss of anticipated profits, consequential damages or incidental damages. For more information and service locations please contact Austin Powder's headquarters:

