



PRODUCT INFORMATION

BROCHURE

1.1D

EMULINE



Emuline is a cap sensitive emulsion explosive which combines Emulex 1 with detonating cord (12 g/m). It was designed for application in contour boreholes, "pre-splitting" and "post-splitting" applications.

PRODUCT OVERVIEW

PROPERTIES

Nominal Density [g/cm ³]	1.05
Mass explosive per meter [kg/m] ¹	0.56
Effective energy [GW/m] ²	3.35

Notes:

¹ Based on Emulex 1.

² For information on the calculations please contact our sales team.

BENEFITS

- Speeds up the loading work, easy handling.
- Smooth blasting, overbreak control.
- No additional preparation necessary, directly applicable.

STANDARD TECHNICAL DESCRIPTION

Diameter [mm]	Total Length [m]	Box Weight NEQ [kg]
25	36	20.5

Notes: Size and weight are nominal values and may show production related variations. Other sizes are available on request.

USE

- Lower temperature limit for application: -20 °C.
- Upper temperature limit application: +60 °C.
- Maximum static overpressure 0.3 MPa (3 bar) for 24 hours.
- Not for underground use.
- Not for use in hazardous environments where flammable gases or dust may exist.
- Austin accepts no responsibility for any loss or liability arising from use of the product in ground containing pyritic or other reactive material.
- The detonating cord tracing the Emuline must be dry. For reliable initiation:
- Detonator with minimum 0.7 g PETN base charge or detonator of comparable strength
- 5 g/m detonating cord or larger attached to the 12 g/m detonating cord that traces the Emuline.

SHELF LIFE, STORAGE & DISPOSAL

- Shelf life is 12 (twelve) months from the date of manufacture.
- This product must be stored in magazines for high explosives. These magazines must meet the current legal requirements.
- In case of presenting the following condition, do not guaranteed the shelf life:
 - Lower temperature limit 0 °C (max. 4 months of storage down to -20 °C).
 - Upper temperature limit: +30 °C.
- Disposal: According to local and national laws. If in doubt consult the supplier.

TRANSPORT – UN CLASSIFICATION

Shipping Name: EXPLOSIVE, TYPE E
 Class & Division: 1.1D
 ID Number: UN 0241

Contact your local Austin Powder representative for further information.

Disclaimer of Warranties and Limitations of Liabilities

Any information contained herein is based on the manufacturer's standard procedures in use at the time of publication. Any specifications, test values and other data is solely preliminary information and not guaranteed. Actual results may differ during field use. Neither manufacturer nor seller will be responsible whatsoever for any losses or damages resulting from the use or reliance upon any information set forth herein.

It is solely the responsibility of the product user to determine the safe conditions for use of the products referred to herein. Use of any products by a user is at the user's sole risk.

To the maximum extent permitted by law, manufacturer and seller specifically disclaim all warranties including implied warranties of merchantability or fitness for a particular purpose.



AUSTIN POWDER

Our Mission is to improve the world we live in through the safe and responsible use of explosives.